

## Weight Indicator

### FEATURES

- Large six-digit LCD display (0.8 in, 21 mm)
- Built-in weighing and counting modes
- Alibi memory retains last 100k transactions
- Drives up to 10 x 350 Ω load cells (4/6 wires) or 20 x 700 Ω load cells
- Two serial ports (RS232) for printing and networking, including various serial stream formats
- Selectable standard Digital I/O with four dry-relay outputs/two opto-isolated inputs
- Standard RS 485, full duplex Interface
- Compatible with digital load cell interface
- 20 mA serial port for a remote display
- Stainless steel enclosure (IP67)
- Custom ticket printing—gross, net and setpoint format can be customized up to 300 characters and print time and date, unit ID, and consecutive ticket number
- Accumulation—weights are totaled, with armed print function
- Batching—up to eight batch steps with latched or continuous outputs for gross, net and delay setpoint. Actions include trip high or low, wait for standstill, print, accumulate and tare
- Keyed tare—preset tare value can be entered when the gross weight is at zero
- Local/remote—remote unit displays weight and transmits key press commands to the local unit
- User and operator password protection
- Audit trail tracking
- Time and date
- Plug and play ready for option card interchange

### OPTIONS

- Rechargeable battery 5.3 A/h, 18 h operation
- Analog output 0/2–10 VDC or 0/4–20 mA
- Additional digital I/O card, four dry-relay outputs/two opto-isolated inputs for setpoints and batching
- Ethernet TCP/IP and USB 2.0 board




### APPLICATIONS

- Bench and floor scales
- Counting scales
- Inventory control
- Process weighing
- Truck scales
- Various industrial systems

### DESCRIPTION

The INTUITION 22i is a versatile, general-purpose weight indicator equipped with a large LCD and a wide range of industrial and commercial applications. With its bluish backlight display, the indicator is the perfect solution for a low-intensity-light environment. In addition, the unit is equipped with an optional rechargeable battery, which allows up to 42 hours of operation time. The 19-key panel enables easy operation, calibration, and setup of the instrument. Two password protection levels allow both the user and operator to access the instrument's setup and configuration menu. An integral printer interface allows easy, programmable, ticket formatting. Automatic date and time storage with the real-time clock option clearly documents all printout records. A broad range of communication interfaces allows streaming and printing in several channels.

### CONFIGURATION



## Weight Indicator

**SPECIFICATIONS****PERFORMANCE****Resolution**

Selectable up to 100000 dd

**Conversion Speed**

5–40 samples per second (selectable)

**Sensitivity**

0.5  $\mu\text{V}/\text{Vsi}$  for approved scales,  
0.1  $\mu\text{V}/\text{Vsi}$  for non-approved scales

**Full Scale Range**

Up to 4 mV/V (20 mV)

**Analog Input Range**

1 mV/V–4 mV/V

**Linearity**

Within 0.01% of full scale

**Excitation**

+5 V  $\pm 0.1$  VDC with sense (6 wires)

**Number of cells**

Up to 10 x 350  $\Omega$  load cells

**Filters**

Rolling average or adaptive filter (selectable)

**Offset Drift**

$\leq 13$  nV/ $^{\circ}\text{C}$

**Span Drift**

$\leq 13$  ppm/ $^{\circ}\text{C}$

**A/D Converter Type**

Sigma-Delta, ratiometric

**Count By**

x1, x2, x5, x10, x20, x50

**Decimal Point**

Between any digits of the weight display

**Calibration Methods**

Dead load and span with optional post calibration tuning of mV/V values

**Weighing Functions**

Automatic zero tracking, motion detection, overload and underload detection, auto-zero on power-up, manual zero, manual tare, preset tare, net mode, unit selection (lb/kg/oz/tn/t/g)

**Operating Modes**

Normal (weigh), piece counting, configuration setup, user menu setup, test

**Supported Applications**

Custom ticket printing, basic weighing, accumulation, batching mode (up to 8 setpoints), preset tare, local and remote

**Supported Features**

Time and date, ALIBI memory (100k weight registrations), audit trail tracking, unit ID, sleep mode with automatic wakeup

**ENVIRONMENTAL****Operating Temperature**

$-10^{\circ}\text{C}$  to  $+40^{\circ}\text{C}$  ( $14^{\circ}\text{F}$  to  $104^{\circ}\text{F}$ )

**Storage Temperature**

$-25^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$  ( $-13^{\circ}\text{F}$  to  $+158^{\circ}\text{F}$ )

**Relative Humidity**

0–95% RH, non-condensing

**DISPLAY AND KEYBOARD****Display**

6 digits, 7 segments, LCD

**Digit Height**

21 mm

**Status Enunciators**

Gross, net, center of zero, standstill, kg/primary units, lb/secondary units, counting, preset tare

**Keypads**

7-functions + 12 numeric keys (standard)

**ELECTRICAL****Voltage**

230 VAC @ 50/60 Hz

**Current (typical)**

2 A

**Power Consumption (typical)**

11 W

**Battery Operation (Optional)**

3.7 V, 5300 mA/h internal rechargeable battery, discharge time 18 h; standby time 56 h (1 x 350  $\Omega$  load cell, no options installed)

**DIGITAL INPUTS AND OUTPUTS****X2 Logic Input per Board**

2 inputs, opto-isolated, up to 24 V input, active-low

**X4 Logic Output per Board**

4 outputs, dry-relay contacts, rating: 2 A, 30 VDC (up to 2 x I/O boards can be installed)

Without removing the standard digital I/O, user can have additional digital I/O as an option making a total of 8 logic outputs (dry-relay contact) or 4 opto-isolated voltage inputs.

**SERIAL COMMUNICATION****Serial Port 1 or 2**

RS-232, programmable

**Serial Port 3**

RS485, programmable  
4/6 wires, fully isolated

**Baud Rate**

9600–19200 bps, full duplex  
7/8 data bits, even/odd/none

## Weight Indicator

### Applications

Printer output, weight output, EDP output, local-remote protocols, and continuous output, remote printer

### Ethernet Port (Optional)

TCP/IP server and client with DHCP

### Applications

Printer output, weight output, EDP output, continuous output, remote printer

### USB 2.0 Port (Optional)

Host PC Device (OTG)

### Applications

Printer output, weight output, EDP output, Load and save configuration data to flash drive

**Note: The Ethernet and USB ports are located on the same optional board.**

### ENCLOSURE—STAINLESS STEEL

#### Dimensions (L x H x D)

9.5 in x 6 in x 2.75 in  
24 cm x 15 cm x 7 cm

#### Mounting

Tilt mount

#### Protection

IP67

#### Wiring Connections

Cable glands

### APPROVALS (ACCURACY CLASS III)

#### OIML R-76

10000d single interval  
Test certificate no.TC8084

CE Marking

### ANALOG OUTPUT (OPTIONAL)

#### Resolution

16 bit DAC

#### Voltage Output

0–10 V

#### Current

0–20 mA or 4–20 mA

#### Linearity

Voltage Output: 0.01% of full scale

Current Output: 0.08% of full scale

#### Offset Drift

Voltage Output:  $\pm 2$  ppm/C° of full scale


Current Output:  $\pm 3$  ppm/C° of full scale

Without removing the standard digital I/O, user can have additional digital I/O as an option making a total of 8 logic outputs (dry-relay contact) or 4 opto-isolated voltage inputs


**Ordering Information is on next page.**

Weight Indicator

**ORDERING INFORMATION FOR INTUITION 22i**



Standard units will come with RS 485 and D I/O as default.



**\*CARD OPTION RESTRICTIONS**

- Maximum of up to two option cards per device can be installed at one time.
- Option card(s) selected in this section will be shipped with the main unit, unassembled.
- See the "Spares and Components" section below for additional card purchase.

**Example Completed Part Numbers:**

22i-S-S-1-NC1-NBT is the part number for a standard, unmodified 22i indicator with the correct power option for the European region.  
 22i-S-S-4-ANA-BAT: unit comes with 220 VAC, China, type I plug; analog O/P card; and with battery, unassembled.  
 22i-S-S-2-ETU-NBT: unit comes with 230 VAC, UK, type G plug; USB card with 4 different cable types; and it does not come with a battery.

**SPARES AND COMPONENTS**



- |   |  |
|---|--|
| RTSP0070 = Bracket for option cards (supports up to two card slots) | RTSP0600 = Digital I/O card installation kit |
| RTSP0580 = USB and Ethernet card installation kit                   | RTSP0090 = Rechargeable battery              |
| RTSP0590 = Analog output card installation kit                      | RTSP0870 = RS485 card installation kit       |

## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at [vpgsensors.com](http://vpgsensors.com).

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.