

## Load Pin

### FEATURES

- Load ranges: 25–60 kN
- Rugged design with zinc-plated, hardened alloy steel construction
- Ratio metric voltage output converter embedded

### APPLICATIONS

- Agriculture equipment
- Force measurement devices
- Off-road vehicles

### DESCRIPTION

The Model 5113 load pin is designed to provide force measurement on an applied load across it. It uses VPG's own internally manufactured, state-of-the-art foil-based strain gages, bonded onto a robust zinc-plated, hardened alloy steel body, making it an ideal sensor for any demanding environment application.


This compact, rugged 38 mm load pin is available in three capacities up to 60 kN and, with a safe overload capability of up to 250 kN, delivers excellent long term stability and reliable operation, even under severe load

conditions. These features make the Model 5113 able to perform repeatable measurements in any given control or safety system.

The Model 5113 load pin is an ideal partner for a wide variety of applications, such as those found in tractor hitch systems, plowing vehicles, cranes or tensioning systems that employ rope, chain or brake anchors. This load pin may be used in lieu of hydraulic pressure or draft pin sensors.



### OUTLINE DIMENSIONS in millimeters




## Load Pin

SPECIFICATIONS				
PARAMETER	VALUE			UNIT
Rated load	±25	±40	±60	kN
Safe overload	±250			kN
Excitation for built-in amplifying circuit	8.0 (recommended)			VDC
Allowed supply voltage	6 ÷ 12			VDC
Maximum current, all conditions	50			mA
Output at zero load (20°C)	4.000 ±0.090			VDC
Output at rated tensile load (20°C)	6.000 ±0.18			VDC
Output at rated compressive load (20°C)	2.000 ±0.18			VDC
Linearity, max. deviation	50			±mV
Hysteresis, max. deviation	50			±mV
Operating temperature range	-30 to +70			°C
Output at zero load	4.000 ±0.1			VDC
Output at rated tensile load	6.000 ±0.26			VDC
Output at rated compressive load	2.000 ±0.19			VDC
EMC, effect at 20°C (per EEG-011)	50			±mV
Environmental protection	IP66			—
Vibration protection, 0 to 2000 Hz	5			g
Endurance test at ±30,000 lb.	1,000,000			Cycles
Storage temperature range	-40 to +85			°C
Cable length	1.42 ±0.02			m
Construction	Hardened alloy steel, zinc plated			—

All specifications are subject to change without notice.

### WIRING SCHEMATIC DIAGRAM



Connector Pin Assignment		
Pin	Color	Function
A	Black	- Excitation
B	White	+ Signal
C	Red	+ Excitation

## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at [vpgsensors.com](http://vpgsensors.com).

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.